

# ContiTrac™

Excellent all-season performance and ride comfort.

Wide, deep tread grooves and a solid center rib provide smooth, stable handling and increased tread life.



## FEATURES & BENEFITS

- **Wide, deep tread grooves**  
Evacuates water away from the tread for confident wet weather driving
- **Specialized tread pitch sequencing**  
Offers smooth, quiet ride
- **Computer aided tread design**  
Remarkable all-season performance and light off-road use

UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	520	A	B

RIM DIAMETER SERIES	OEM	SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	TIRE WEIGHT (kg)	TIRE WEIGHT (lbs)	MAX INFLATION PRESSURE (psi)	OVERALL SECTION WIDTH (meas. rim) (in.)	APPROVED RIM WIDTHS (in.)	MAX LOAD (kg)	MAX LOAD (lbs)	MAX DUAL LOAD (kg)	MAX DUAL LOAD (lbs)	TREAD DEPTH (32nds)	REVS PER MILE	
<b>ContiTrac™</b>																			
15	70	Ford	P225/70R15	100S	SL	BSW	15473440000	27.4	11.2	24.6	44	9.0 (6.5)	6.0 - 7.5	800	1764			11/32	761
		Ford	P225/70R15	100S	SL	OWL	15473450000	27.4	11.4	25.1	44	9.0 (6.5)	6.0 - 7.5	800	1764			11/32	761
16	70	Ford	P235/70R16	104T	SL	OWL	15481000000	29.0	13.6	29.9	44	9.4 (7.0)	6.0 - 8.0	900	1984			12/32	719
		Ford	P235/70R16	104T	SL	BSW	15482500000	29.0	13.2	29.2	44	9.4 (7.0)	6.0 - 8.0	900	1984			12/32	719
17	75	Ford	LT245/75R17	121/118S	E	BSW	04320080000	31.5	19.5	42.9	80	9.7 (7.0)	6.0 - 7.5	1450	3197	1320	2910	13/32	662
18	70	Nissan	P265/70R18	114S	SL	BSW	15482600000	32.6	17.0	37.6	44	10.7 (8.0)	7.0 - 9.0	1180	2601			11/32	640
		Ford	LT275/70R18	125/122S	E	BSW	04320060000	33.2	23.8	52.4	80	10.9 (8.0)	7.0 - 8.5	1650	3638	1500	3307	14/32	628
65	Ford	LT275/65R18	123/120S	E	BSW	04320090000	32.1	23.1	51.0	80	10.9 (8.0)	7.0 - 8.5	1550	3417	1400	3086	14/32	650	
<b>ContiTrac™ SUV</b>																			
17	70	Ford	P265/70R17	113S	SL	BSW	15449890000	31.6	17.0	37.6	44	10.7 (8.0)	7.0 - 9.0	1150	2535			12/32	660
<b>ContiTrac™ TR (shown)</b>																			
70	Ford	P265/70R17	113S	SL	OWL	15449900000	31.6	18.1	40.0	44	10.7 (8.0)	7.0 - 9.0	1150	2535			13/32	660	
17	65	GM	P245/65R17	105S	SL	BSW	15448940000	29.5	14.0	30.8	44	9.8 (7.0)	7.0 - 8.5	925	2039			12/32	707
		GM	P245/65R17	105S	SL	OWL	15448950000	29.5	14.5	31.9	44	9.8 (7.0)	7.0 - 8.5	925	2039			12/32	707
18	70	Ford	LT275/70R18	125/122S	E	BSW	04320020000	33.2	24.1	53.1	80	10.9 (8.0)	7.0 - 9.0	1650	3638	1500	3307	15/32	628
		Ford	LT275/70R18	125/122S	E	BSW	04569060000	33.2	24.4	53.7	80	10.9 (8.0)	7.0 - 9.0	1650	3638	1500	3307	15/32	628



\* Tires with Load/Speed Index in parenthesis are Z speed rated. The number in the parenthesis is the equivalent speed index.