

# Conti4x4SportContact™

The definition of responsiveness.

Original equipment on some of the world's finest SUVs this tire supports high speed cornering and stability.

## FEATURES & BENEFITS

- **Asymmetrical tread design with compact outer shoulder blocks**  
Aids in cornering stability and control
- **Continuous center tread ribs**  
Delivers precise steering response and high speed stability
- **Wide longitudinal and lateral water evacuation grooves**  
Provide resistance to hydroplaning
- **Offset tread blocks and grooves**  
Produces a smooth, quiet ride
- **Rim flange rib protector**  
Protects the rim from curb damage



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	280	A	A

RIM DIAMETER	SERIES	OEM	SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	TIRE WEIGHT (kg)	TIRE WEIGHT (lbs)	MAX INFLATION PRESSURE (psi)	OVERALL SECTION WIDTH (meas. rim) (in.)	APPROVED RIM WIDTHS (in.)	MAX LOAD (kg)	MAX LOAD (lbs)	TREAD DEPTH (32nds)	REVS PER MILE
<b>Conti4x4SportContact™</b>																	
19	45	Porsche	275/45R19	108Y	XL	BSW	03546310000	28.7	15.3	33.8	51	10.7 (9.0)	8.5 - 10.5	1000	2205	10/32	726
20	40	Porsche	275/40R20	106Y	XL	BSW	03546370000	28.7	15.3	33.8	51	10.9 (9.5)	9.0 - 10.5	950	2094	10/32	726
		LandRover	275/40R20	106Y	XL	BSW	03546580000	28.7	15.6	34.4	51	10.9 (9.5)	9.0 - 10.5	950	2094	10/32	726