

ContiTouringContact™ CH, CT, CV, CW95

Perfect for performance touring cars.

This innovative tire offers a smooth, low noise ride and reduced rolling resistance for increased fuel efficiency.

FEATURES & BENEFITS

- **Proven performance**
Selected as original equipment fitments by many major European automobile manufacturers
- **Tri-radial tread contour**
Provides better wear, quieter ride, and greater resistance to hydroplaning
- **Weight-optimized construction**
Lowers rolling resistance and enhances fuel economy
- **Spiral-wound, jointless nylon cap plies**
Provide uniformity and high-speed integrity

UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	360	A	A



RIM DIAMETER	SERIES	OEM	SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	TIRE WEIGHT (kg)	TIRE WEIGHT (lbs)	MAX INFLATION PRESSURE (psi)	OVERALL SECTION WIDTH (meas. rim) (in.)	MAX I. LOAD (kg)	MAX I. LOAD (lbs)	TREAD DEPTH (32nds)	REVS PER MILE	DESIGN	
ContiTouringContact™ - CH95, CT95, CV95, CW95																		
16	55	Volvo	205/55R16	91V	SL	BSW	03512330000	24.9	8.5	18.6	51	8.4 (6.5)	5.5 - 7.5	615	1356	10/32	831	CV95
		Mercedes	225/55R16	95H	SL	BSW	03515740000	25.7	9.5	21.0	51	9.2 (7.0)	6.0 - 8.0	690	1521	10/32	811	CH95
	50	Mercedes	225/50R16	92H	SL	BSW	03511480000	24.9	9.0	19.8	51	9.2 (7.0)	6.0 - 8.0	630	1389	10/32	831	CH95
17	65	Ford	P215/65R17	98T	SL	BSW	15473880000	28.0	11.2	24.6	44	8.6 (6.5)	6.0 - 7.5	750	1654	10/32	745	CT95
	60	Ford	P215/60R17	95T	SL	BSW	15482710000	27.2	9.9	21.8	44	9.3 (6.5)	6.0 - 7.5	690	1521	10/32	767	CT95
	55	Nissan	P225/55R17	95V	SL	BSW	15475480000	26.7	9.5	21.0	44	9.3 (7.0)	6.0 - 8.0	690	1521	10/32	781	CV95
	45	Mercedes	245/45R17	95H	SL	BSW	03515390000	25.7	10.3	22.6	51	9.6 (8.0)	7.5 - 9.0	690	1521	10/32	811	CH95
18	40	Chrysler	225/40R18	92W	XL	BSW	03522500000	25.1	9.6	21.1	51	9.0 (8.0)	7.5 - 9.0	630	1389	10/32	825	CW95
19	35	Chrysler	255/35R19	92W	SL	BSW	03520660000	26.0	10.9	24.0	51	10.4 (9.0)	8.5 - 10.0	630	1389	10/32	802	CW95