

Vanco™ 2

Robust, versatile, long wearing.

The Vanco™ 2 sets new benchmarks in efficiency and performance for van tires.

FEATURES & BENEFITS

- **Advanced tread compound technology**
Promotes improved driving performance and handling. Long tread life
- **Wide circumferential grooves**
Outstanding protection in wet conditions
- **Versatile tread design**
Allows performance on multiple road surfaces



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	300	A	A

RIM DIAMETER SERIES	OEM	SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE/WHEEL DIAMETER (in.)	TIRE WEIGHT (kg)	TIRE WEIGHT (lbs)	MAX INFLATION PRESSURE (psi)	OVERALL SECTION WIDTH (meas. r/rm) (in.)	APPROVED RIM WIDTHS (in.)	MAX LOAD (kg)	MAX LOAD (lbs)	MAX DUAL LOAD (kg)	MAX DUAL LOAD (lbs)	TREAD DEPTH (32nds)	REVS PER MILE
Vanco™ 2																		
14		185R14C	102/100Q	D	BSW	04511500000	25.7	9.3	20.6	65	7.4 (5.5)	5.0 - 6.0	850	1874	800	1764	11/32	808
		125/70R15	109/107R	D	BSW	45115500000	26.9	13.2	29.1	65	8.7 (6.5)	5.5 - 7.0	1030	2271	975	2149	12/32	772
15	70	195/70R15	104/102R	D	BSW	45115400000	25.7	11.2	24.8	65	7.9 (6.0)	5.0 - 6.0	900	1984	850	1874	12/32	808
		225/70R15	112/110R	D	BSW	45115600000	27.4	14.0	31.0	65	9.0 (6.5)	6.0 - 7.5	1120	2469	1060	2337	12/32	758
15	65	205/65R15	102/100T	C	BSW	04510180000	25.5	10.4	22.8	55	8.2 (6.0)	5.5 - 7.5	850	1874	800	1764	11/32	815
16	65	215/65R16	109/107R	D	BSW	04511620000	27.0	11.9	26.2	70	8.7 (6.5)	6.0 - 7.5	1030	2271	975	2149	11/32	769