


HDL Eco Plus (Heavy Drive Long-Haul)



- Advanced tread compound provides long original mileage and low rolling resistance
- Closed shoulder tread design provides even tread wear while still providing excellent traction
- Stone ejection system reduces stone retention and casing penetrations
- 28/32" tread depth for optimized mileage and rolling resistance



Applications:

Long haul, over the highway drive position

TIRE SPECIFICATIONS

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX SPEED (MPH)#	STATIC LOADED RADIUS IN (MM)	OVERALL INFLATED DIAMETER IN (MM)	OVERALL INFLATED WIDTH IN (MM)	LOADED SECTION WIDTH IN (MM)	APPROVED RIMS	MINIMUM DUAL SPACING IN (MM)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION SINGLE LBS (KG)	DUAL PSI (KPA)	DUAL LBS (KG)	DUAL PSI (KPA)
-----------	------------	----------------	---------------------	------------------	------------------------------	-----------------------------------	--------------------------------	------------------------------	---------------	------------------------------	--------------------	---------------------	------------------------------------	----------------	---------------	----------------

TUBELESS TIRE ON 15 DEGREE CENTER RIMS

11R22.5*	G	05682990000	28	75	19.6 (498)	42.0 (1066)	11.1 (282)	12.1 (307)	8.25	12.5 (318)	493 (306)	127 (58)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5*	H	05683750000	28	75	19.6 (498)	42.0 (1066)	11.1 (282)	12.1 (307)	8.25	12.5 (318)	493 (306)	127 (58)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
275/80R22.5*	G	05683980000	28	75	18.9 (480)	40.8 (1036)	11.0 (279)	12.1 (307)	8.25	12.5 (318)	509 (315)	119 (54)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
275/80R22.5*	H	05683770000	28	75	18.9 (480)	40.8 (1036)	11.0 (279)	12.1 (307)	8.25	12.5 (318)	509 (315)	119 (54)	6940 (3150)	120 (830)	6175 (2800)	120 (830)
11R24.5	G	05683400000	28	75	20.6 (523)	44.0 (1117)	11.1 (282)	12.1 (307)	8.25	12.5 (318)	470 (292)	135 (61)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
11R24.5	H	05683760000	28	75	20.6 (523)	44.0 (1117)	11.1 (282)	12.1 (307)	8.25	12.5 (318)	470 (292)	136 (62)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
285/75R24.5	G	05683990000	28	75	19.6 (498)	42.0 (1066)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	493 (306)	128 (58)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
285/75R24.5	H	05683780000	28	75	19.6 (498)	42.0 (1066)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	493 (306)	128 (58)	6780 (3075)	120 (830)	6175 (2800)	120 (830)
305/75R24.5	H	05681610000	29	75	20.2 (513)	43.2 (1097)	11.4 (289)	12.5 (316)	8.25	13.1 (333)	479 (298)	141 (64)	7830 (3550)	125 (860)	6945 (3150)	115 (790)

NOTE - RIM LISTED FIRST IS THE MEASURING RIM. MINIMUM DUAL SPACING CALCULATED WITHOUT CHAINS.
 * - ECE CERTIFIED. # - EXCEEDING THE LAWFUL SPEED LIMIT IS NEITHER RECOMMENDED OR ENDORSED.
 OVERALL WIDTHS WILL CHANGE 0.1 INCH (2.5 MM) FOR EACH 1/4 INCH CHANGE IN RIM WIDTH. MINIMUM DUAL SPACING SHOULD BE ADJUSTED ACCORDINGLY.
 CONTINENTAL TIRE NORTH AMERICA, INC. RESERVES THE RIGHT TO CHANGE PRODUCT SPECIFICATIONS AT ANY TIME WITHOUT NOTICE OR OBLIGATIONS.
 PLEASE CONSULT RIM MANUFACTURERS LOAD AND INFLATION LIMITS. NEVER EXCEED RIM MANUFACTURERS LIMITS WITHOUT PERMISSION OF COMPONENT MANUFACTURER.