



## HSL2 (Heavy Steer Long-Haul)

- FlexLock™ technology features an interlocking mechanism that promotes even tread wear
- Advanced compounding with low rolling resistance contributes to fuel efficiency
- New, innovative tread compound provides significant increase in removal mileage
- Visual Alignment Indicators (VAI®) alert user of tire tracking problems



### Applications:

Long haul and over the highway steering and all-position use

### TIRE SPECIFICATIONS

TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32NDS)	MAX SPEED (MPH)#	STATIC LOADED RADIUS IN (MM)	OVERALL INFLATED DIAMETER IN (MM)	OVERALL INFLATED WIDTH IN (MM)	LOADED SECTION WIDTH IN (MM)	APPROVED RIMS	MINIMUM DUAL SPACING IN (MM)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION SINGLE LBS (KG)	DUAL PSI (KPA)	DUAL LBS (KG)	DUAL PSI (KPA)
-----------	------------	----------------	---------------------	------------------	------------------------------	-----------------------------------	--------------------------------	------------------------------	---------------	------------------------------	--------------------	---------------------	------------------------------------	----------------	---------------	----------------

#### TUBELESS TIRE ON 15 DEGREE CENTER RIMS

11R22.5*	G	05685990000	19	75	19.3 (489)	41.4 (1052)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	500 (311)	117 (53)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5*	H	05686030000	19	75	19.3 (489)	41.4 (1052)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	500 (311)	119 (54)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
275/80R22.5*	G	05686010000	19	75	18.6 (472)	40.1 (1019)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	516 (321)	112 (51)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
275/80R22.5*	H	05686050000	19	75	18.6 (472)	40.1 (1019)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	516 (321)	113 (51)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
11R24.5	G	05686000000	19	75	20.2 (513)	43.4 (1102)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	477 (296)	125 (57)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
11R24.5	H	05686040000	19	75	20.3 (516)	43.4 (1102)	11.1 (282)	12.2 (310)	8.25	12.5 (318)	477 (296)	127 (58)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
285/75R24.5	G	05686020000	19	75	19.4 (493)	41.4 (1052)	11.0 (279)	12.0 (305)	8.25	12.5 (318)	500 (311)	115 (52)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
285/75R24.5	H	05686060000	19	75	19.4 (493)	41.4 (1052)	11.0 (279)	12.0 (305)	8.25	12.5 (318)	500 (311)	117 (53)	6780 (3075)	120 (830)	6175 (2800)	120 (830)
295/60R22.5* (‡)	J	05110040000	18	75	16.8 (427)	37.0 (940)	11.5 (292)	12.0 (304)	9.00	12.9 (328)	561 (348)	105 (48)	7390 (3550)	130 (900)	6780 (3075)	130 (900)
315/80R22.5* (**)	J	05684480000	18	75	19.7 (500)	42.4 (1076)	12.3 (312)	12.9 (328)	9.00, 8.25	13.8 (351)	489 (304)	130 (59)	8270 (3750)	120 (830)	7385 (3350)	120 (830)
315/80R22.5* (+)	J	05110010000	19	75	19.7 (500)	42.4 (1076)	12.3 (312)	12.5 (318)	9.00, 8.25	13.9 (355)	491 (305)	135 (61)	8270 (3750)	120 (830)	7385 (3350)	120 (830)

NOTE - RIM LISTED FIRST IS THE MEASURING RIM. MINIMUM DUAL SPACING CALCULATED WITHOUT CHAINS.  
 \* - ECE CERTIFIED. # - EXCEEDING THE LAWFUL SPEED LIMIT IS NEITHER RECOMMENDED OR ENDORSED.  
 OVERALL WIDTHS WILL CHANGE 0.1 INCH (2.5 MM) FOR EACH 1/4 INCH CHANGE IN RIM WIDTH. MINIMUM DUAL SPACING SHOULD BE ADJUSTED ACCORDINGLY.  
 315/80R22.5 TIRES USED ON 8.25" RIMS ARE RESTRICTED TO A MAXIMUM OF 7610 LBS AT 120 PSI.  
 ‡ TREAD PATTERN VARIES \*\* TREAD PATTERN VARIES - HSL ECO PLUS NOMENCLATURE + TREAD PATTERN VARIES - HSL1 ECO PLUS NOMENCLATURE  
 CONTINENTAL TIRE NORTH AMERICA, INC. RESERVES THE RIGHT TO CHANGE PRODUCT SPECIFICATIONS AT ANY TIME WITHOUT NOTICE OR OBLIGATIONS.  
 PLEASE CONSULT RIM MANUFACTURERS LOAD AND INFLATION LIMITS. NEVER EXCEED RIM MANUFACTURERS LIMITS WITHOUT PERMISSION OF COMPONENT MANUFACTURER.