

» ContiEcoContact3

Product Overview

- TR / HR rated
- 13" - 15" diameter
- Targeted at mini, super-mini and lower medium vehicle class
- Asymmetric tread pattern
- Excellent traction on wet and dry roads
- Safety when braking and cornering
- Lower fuel consumption due to reduced rolling resistance
- Wide range of O.E. approvals



Key features, advantages and benefits

Product feature	Effect	Customer benefit
Asymmetrical tread pattern design with circumferentially stiff tread pattern centre and compact outer shoulder.	➤ Optimum ground contact.	➤ Shorter braking distance on dry and wet roads.
Wide circumferential grooves arranged into the centre of the tyre pattern.	➤ Improved water expulsion.	➤ Increased security on wet roads.
Innovative, flexible silica compound with high dynamic stiffness and new polymer concept.	➤ Lower rolling resistance.	➤ Excellent traction on wet and dry roads. Lower fuel consumption.
Contour based on flat belt concept	➤ Minimised tread pattern deformation when tyre is rolling. Uniform wear pattern.	➤ Safety when braking and cornering. Lower wear rate giving a longer life.

Range available

Series	Speed Rating	Diameter (inches)	Width (mm)
80 Series	TR	13" - 14"	145 - 175
70 Series	TR/HR	13" - 15"	145 - 185
65 Series	TR/HR	13" - 15"	155 - 195
60 Series	TR/HR	14" - 16"	165 - 185