

Conti 4x4 SportContact™

THE DEFINITION OF RESPONSIVENESS

EXCELLENT HIGH CORNERING AND HIGH-SPEED CONTROL ARE BENEFITS OF THIS TIRE THAT SERVES AS ORIGINAL EQUIPMENT ON THE WORLD'S FINEST VEHICLES.



UTQG:	TREAD:	TRACTION:	TEMPERATURE:
ALL SIZES	280	A	A

FEATURES:	BENEFITS:
• Asymmetrical tread design with compact outer shoulder blocks	• Enhances cornering stability and control
• Continuous center tread ribs	• Delivers precise steering response and high speed stability
• Wide longitudinal and lateral water evacuation grooves	• Provide maximum resistance to hydroplaning
• Optimized offset tread blocks and grooves	• Provide smooth, quiet ride
• Rim flange rib protector	• Protects the rim from curb damage

	ORIGINAL EQUIPMENT FITMENTS	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (MEASURING RIM) (in)	APPROVED RIM WIDTHS (in)	TREAD DEPTH (in - 32nds)	REVS PER MILE
Porsche	18	55	255/55R18	109Y	XL	BSW	03546250000	26.8	16.0	35.1	51	9.2 (7.0)	6.0 - 8.0	11/32	778	
Porsche	19	45	275/45R19	108Y	XL	BSW	03546310000	28.8	16.1	35.3	51	10.7 (9.0)	8.5 - 10.5	10/32	724	
		35	315/35ZR20	ZR	XL	BSW	03546300000	28.7	15.0	33.0	51	12.6 (11.0)	10.5 - 12.5	10/32	726	
Porsche	20	40	275/40R20	106Y	XL	BSW	03546370000	28.7	16.0	35.2	51	10.9 (9.5)	9.0 - 10.5	10/32	726	
LandRover			275/40R20	106Y	XL	BSW	03546580000	28.7	16.0	35.2	51	10.9 (9.5)	9.0 - 10.5	10/32	726	