

ContiCrossContact™ UHP

THE ULTIMATE IN STYLE AND PERFORMANCE
THIS TIRE DELIVERS STABILITY, CONTROL AND
RESPONSIVENESS AT THE HIGHEST LEVEL.



UTQG:	TREAD:	TRACTION:	TEMPERATURE:
ALL SIZES	420	AA	A

FEATURES:	BENEFITS:
<ul style="list-style-type: none"> Asymmetric tread with wide circumferential grooves 	<ul style="list-style-type: none"> Enhances grip for braking and reduces risk of hydroplaning
<ul style="list-style-type: none"> Bionic contour 	<ul style="list-style-type: none"> Reduces braking distances and improves cornering stability
<ul style="list-style-type: none"> Advanced silica technology 	<ul style="list-style-type: none"> Lowers rolling resistance and enhances wet and dry grip
<ul style="list-style-type: none"> Rim flange rib protector 	<ul style="list-style-type: none"> Protects expensive rims from curb damage

ORIGINAL EQUIPMENT FITMENTS	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (MEASURING RIM) (in)	APPROVED RIM WIDTHS (in)	TREAD DEPTH (in - 32nds)	REVS PER MILE
Land Rover	18	55	255/55R18	109V	XL	BSW	03546920000	29.0	14.0	30.8	51	10.4 (8.0)	7.0 - 9.0	10/32	715
Mercedes			255/55R18	105W	SL	BSW	03546950000	29.0	16.0	35.2	51	10.4 (8.0)	7.0 - 9.0	11/32	718
Range Rover	19	50	255/50R19	107Y	XL	BSW	03546380000	29.1	15.2	33.4	51	10.4 (8.0)	7.0 - 9.0	10/32	712
Mercedes			255/50R19	103W	SL	BSW	03546000000	Coming early 2006							