

GENERAL TIRE 

S580




GENERAL TIRE
MEDIUM TRUCK


S580

LONG HAUL STEER

Visual Alignment Indicators (VAI®) alert users to tire tracking problems.



Stone ejection system reduces stone retention and casing penetrations.



18/32" 6 rib tread design provides long mileage and low rolling resistance.



Applications:

Long haul, over-the-highway steering and all-position use.

TIRE SPECIFICATIONS Highway - 75 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
													lbs (KG)	psi (KPa)	lbs (KG)	psi (KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5	G	18/32	0211358	05684410000	8.25	41.3 (1049)	11.0 (279)	12.2 (310)	19.4 (493)	12.5 (318)	500 (311)	116 (53)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5	H	18/32	0211359	05684420000	8.25	41.3 (1049)	11.0 (279)	12.2 (310)	19.4 (493)	12.5 (318)	500 (311)	116 (53)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	G	18/32	0211360	05684430000	8.25	43.4 (1102)	11.0 (279)	12.2 (310)	20.4 (518)	12.5 (318)	475 (295)	122 (55)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
11R24.5	H	18/32	0211361	05684440000	8.25	43.4 (1102)	11.0 (279)	12.2 (310)	20.4 (518)	12.5 (318)	475 (295)	123 (56)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
295/75R22.5	G	18/32	0211362	05684450000	8.25	40.1 (1019)	11.0 (279)	12.2 (310)	18.7 (475)	12.5 (318)	515 (320)	106 (48)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
295/75R22.5	H	18/32	0211363	05684460000	8.25	40.1 (1019)	11.0 (279)	12.2 (310)	18.7 (475)	12.5 (318)	515 (320)	107 (49)	6940 (3150)	120 (830)	6175 (2800)	120 (830)
285/75R24.5	G	18/32	0211365	05684470000	8.25	41.3 (1049)	10.8 (274)	11.9 (302)	19.3 (490)	12.5 (318)	500 (311)	114 (52)	6175 (2800)	110 (760)	5675 (2575)	110 (760)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.