

GENERAL TIRE



D445



GENERAL TIRE
MEDIUM TRUCK

D445

GENERAL PURPOSE DRIVE

Aggressive tread pattern offers excellent all-weather traction.

Block/rib designed shoulder provides reduced driving noise and promotes even wear.

Multi-service tread compound provides long tread life in on/off road conditions.



Applications:

Drive position short and long haul. On/off highway service (depending on conditions).

TIRE SPECIFICATIONS Highway - 65 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
													KG	psi	KG	psi
TUBETYPE TIRES ON TYPE I, II, III RIMS																
9.00R20	G	26/32	0117055	05391030000	7.00	40.1 (1018)	10.2 (258)	10.5 (267)	18.5 (471)	11.9 (301)	516 (320)	126 (57)	5675 (2575)	115 (790)	5355 (2430)	115 (790)
10.00R20	H	26/32	0117058	05391050000	7.50	41.4 (1052)	10.8 (275)	11.1 (283)	19.1 (485)	12.6 (319)	500 (310)	136 (61)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11.00R20	H	26/32	0111252	05391080000	8.00	42.6 (1082)	11.3 (286)	12.0 (304)	19.6 (498)	13.4 (341)	486 (302)	145 (65)	7390 (3350)	120 (830)	6780 (3075)	120 (830)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
10R22.5	G	23/32	0111249	05680630000	7.50	40.3 (1024)	9.9 (251)	10.8 (274)	18.6 (472)	11.4 (290)	514 (319)	104 (47)	5675 (2575)	115 (790)	5355 (2430)	115 (790)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.