

GENERAL TIRE 

S371



GENERAL TIRE
MEDIUM TRUCK

S371

ALL-POSITION REGIONAL

Visual Alignment Indicators (VAI®) aids in early detection of tire tracking problems.

Unique stone ejection system reduces stone retention.

Tread compound specially formulated to provide high mileage for on-highway driving, and resists cuts and tears in off-road use.



Applications:

Bottom dumps, end dumps, coal haulers, school buses, waste haulers, beverage trucks, local delivery.

TIRE SPECIFICATIONS Highway - 65 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													Single lbs (KG)	psi (KPa)	Dual lbs (KG)	psi (KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
11R22.5	H	20/32	0238403	05685910000	8.25	41.4 (1052)	11.1 (281)	11.9 (302)	19.3 (490)	12.5 (318)	500 (311)	118 (54)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
11R24.5	H	20/32	0238405	05685920000	8.25	43.4 (1103)	11.1 (281)	11.9 (302)	20.3 (516)	12.5 (318)	477 (296)	128 (58)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
295/75R22.5	H	20/32	0238387	05685930000	8.25	40.1 (1019)	11.0 (279)	12.5 (318)	18.6 (472)	12.5 (318)	516 (321)	113 (51)	6940 (3150)	120 (830)	6175 (2800)	120 (830)
285/75R24.5	H	20/32	0238390	05685940000	8.25	41.3 (1049)	10.8 (274)	12.0 (305)	19.3 (490)	12.5 (318)	501 (311)	118 (53)	6780 (3075)	120 (830)	6175 (2800)	120 (830)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.