

GENERAL TIRE 

LMT 450



GENERAL TIRE
MEDIUM TRUCK

LMT 450

TRACTION DRIVE

Drive positions, 18/32 tread pattern provides long mileage in regional and local service.

Aggressive open shoulder pattern provides great traction in mud, snow and off-road conditions.



Applications:
Commercial Duty light trucks.

TIRE SPECIFICATIONS Highway - 81 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
												lbs (KG)	psi (KPa)	lbs (KG)	psi (KPa)	
225/70R19.5*	F	18/32	0130320	05682420000	6.00	32.0 (813)	8.2 (208)	9.3 (236)	15.0 (381)	10.0 (254)	647 (402)	58 (26)	3640 (1650)	95 (660)	3415 (1550)	95 (660)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.

*ECE Certified