

GENERAL TIRE 

LMT 460



GENERAL TIRE
MEDIUM TRUCK

LMT 460

ALL-POSITION SERVICE

All position, 18/32 tread pattern provides excellent traction and handling in both on and off road conditions.

Button/Rib tread design provides excellent traction and handling.

Closed shoulder tread design provides even wear and reduced noise.



Applications:
Commercial duty light trucks.

TIRE SPECIFICATIONS Highway - 81 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
												lbs (KG)	psi (KPa)	lbs (KG)	psi (KPa)	
225/70R19.5*	F	18/32	0159922	05682400000	6.00	32.0 (813)	8.2 (208)	9.3 (236)	15.0 (381)	10.0 (254)	647 (402)	60 (27)	3640 (1650)	95 (660)	3414 (1550)	95 (660)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.

*ECE Certified.